

LUX BITOLA® Cold Banquet Trolleys



Rating: Not Rated Yet

Price:

Variant price modifier:

Base price with tax:

Price with discount:

Salesprice with discount:

Sales price:

Sales price without tax:

Discount:

Tax amount:

[Ask a question about this product](#)

Description

- Working temperature; 0° C, + 5° C (at ambient temp.43° C)
- 220 V-230 V -1 +N -50 60 Hz electrical power.
- “CFC Free” , R-134 A refrigerant gas.
- Operating voltage : 220 V
- Digital thermostat control unit.
- Magnetic locker.
- Lockable castors provide stabilizing.
- Isolation type:40 kg/m3 density polyurathane isolation.
- Pressed interior tray slides.
- Stainless steel body.

CD oe ds ec ri p ti o n	Dimensions mm			NPC eo a t w p ea r ci k g kty w
	a	b	c	
EC 720x 1101				
ol885x 3 . . 1				
d 1830 113 x				

Preparation : LUX BITOLA®; Cold Banquet Trolleys

B 65G
a N
n 2
q /
u 1
e
t
T
r
ol
le
y
EC 1360 2 2 0 2
olx885 4 . . x
d x183 0 2 7 ()
B 0 0 1
a 1
n x
q G
u N
e 2
t /
T 1
r)
ol
le
y
EC 720x8 0 0 6
ol885x0 . . x
d 1250 7 3 G
B 9 5 N
a 2
n /
q 1
u
e
t
T
r
ol
le
y
EC 505x1 0 0 1
ol775x0 . . 5
d 1830 5 7 3 x
B 15 G
a N
n 1
q /
u 1
e
t
T
r
ol
le
y

Reviews

There are yet no reviews for this product.