

LUX BITOLA® Refrigerated Counters With Sink



Rating: Not Rated Yet

Price:

Variant price modifier:

Base price with tax:

Price with discount:

Salesprice with discount:

Sales price:

Sales price without tax:

Discount:

Tax amount:

[Ask a question about this product](#)

Description

- Working temperature; 0° C , + 5° C (at ambient temp. 43° C)
- 220 V-230 V -1 +N -50 60 Hz electrical power.
- "CFC Free" , R-134 A refrigerant gas.
- 40 kg/m3 density.
- Electronic temperature and defrosting control and display.
- Automatic evaporation of water during defrosting.
- Removable, conditioning compressor.
- Fan cooling.
- "Ozone-friendly" 48 mm thickness polyurethane isolation.
- Self closing doors.
- Smooth front top edges.
- Copper tube evaporator with aluminum fins.
- Adjustable, stainless steel shelf housing, plastic coated shelves.
- Stainless steel body.

CD	Dimensions	NPCS
oe	mm	eoain
ds		twpk
ec		eaD
ri		k r ci i
p		g kty
ti		wlt
o		
n		



ER150090033
ex7005 . . 05
frx850 9300
ig 5 x
e 4
r 0
a 0
t
e
d
C
o
u
n
t
e
r

ER200011053
ex7002 . . 05
frx85002300
ig 5 x
e 4
r 0
a 0
t
e
d
C
o
u
n
t
e
r

ER255011073
ex7004 . . 05
frx85055500
ig 0 x
e 4
r 0
a 0
t
e
d
C
o
u
n
t
e
r

Reviews

There are yet no reviews for this product.